

Tradewaste Flowmeters

Compliant to Sydney Water requirements


To assist selection advise us:

- pipe diameter e.g. 50mm;
- pipe type e.g. PVC, Poly, Galvanised Iron;
- approx. min & max flowrate in Litres/min;
- approx. discharge volume in Litres/day.

We customise
the flowmeter
for your application



Flowmeter is delivered ready to install:

- ☺ With Sydney Water special tradewaste sampler plugs fitted. 
- ☺ Fully programmed to Sydney Water specifications.
- ☺ Integral or Remote Display options with Sensor Prewired to Display, with 2mtr standard cable length (longer on request)
- ☺ With Flanged Connection Kit (if requested).
- ☺ Wet Tested (certificate supplied).
Follow-up Onsite verification service.

Additional Service

ManuFlo yearly on-site flowmeter verification service.

For pipe sizes:

25, 40, 50, 80, 100 & 150mm

with optional connection kits PVC Slip flanges with S/S earth-ring, gaskets, bolted to sensor ready to go for easy plumbing install.

Technical details

- **Pipe sensor:** Obstructionless bore (virtually maintenance free).
WAFFER or FLANGED options.
- **Display:** includes Total and Flowrate.
- **Connection Kit:**
Includes flanges, bolts, gaskets, S/S-ring.
- **Power:** 85 - 253vac or 24VDC

ManuFlo®™

Flow Measurement & Control Products

- Sydney-based company, founded in 1965.
- One of the founding companies in tradewaste measurement (1984).

41 Carter Road, Brookvale
Sydney NSW 2100 Australia
Ph: + 61 2 9905-4324, 9938-1425
Fax: + 61 2 9938-5852

Web: www.manuelectronics.com.au
Email: sales@manuelectronics.com.au