NMI M10 Australian Pattern Approved



Are your flowmeters compliant with NMI M10 Australian Pattern Approval which is the legislated Australian Standards requirement for rural water meters as laid out in the National Framework for Non-Urban Water Metering? If not ManuFlo can assist you with local stock of two different types of flowmeter technologies namely a mechanical 'Turbine' type or alternatively Electro-magnetic type which has no moving parts at all.

ELECTRO-MAGNETIC

KMS703 Flowmeters


- Electro-magnetic, no moving parts.
- Battery Powered (long life Lithium +8 years)
- LCD Flow Rate & volume Totals + and -.
- Ideal for dirty water & gravitational flows or low pressure applications for irrigation.
- Sizes 25 to 300mm
- Accuracy ±0.5% of reading
- Optional Voltage free pulse output.

TURBINE

WPD Flowmeters

- Turbine mechanical turning movement.
- Running mechanical register volume Total m3.
- · Ideal for gravitational flows or low pressure applications for irrigation.
- Sizes 40-300mm.
- · Accuracy ±2.5% of reading.
- Optional Voltage free pulse output









NMI-M10 AS4747

Australian Pattern



Spinning Turbine









Size	Flowrange (Litres/min) / Accuracy	
Order Code	min (±2%)	Max (±0.5%)
KMS703-025F	0.7	267
KMS703-040F	1.6	667
KMS703-050F	2.6	1000
KMS703-065F	4.2	1666
KMS703-080F	7	2666
KMS703-100F	11	4167
KMS703-150F	27	10500
KMS703-200F	42	10800
KMS703-250F	66	16667
KMS703-300F	106	26666

Note: Also available in externally powered versons 240 VAC or 24 VDC, contact ManuFlo for details.







Size	Flowrange (L/min) / Accuracy		
Order Code	min ±5%	min ±2%	max ±2%
WPD-40	4	7	666
WPD-50	5	12	833
WPD-65	7	13	1167
WPD-80	8	15	2000
WPD-100	13	30	3833
WPD-150	50	67	7500
WPD-200	67	100	13333
WPD-250	100	183	20833
WPD-300	200	250	23300

Note: Refer page 2 for Manuflo digital resettable counters

Wired to ManuFlo LCD Resettable Totalizers, Loggers, Batch Ticket Printers for Transfers/Monitoring

ME5-T Resettable LCD Indicator

Power	Lithium Battery (+9 yrs)
Mounting	Wall mount to IP67
Display	5 Digit LCD counter
Reset Function	Push button on front
Units	Litres or Kilolitres

10000 Market




ME4-T Resettable LCD Indicator

Power	Lithium Battery (+9 yrs)
Mounting	Wall mount to IP67
Display	4 Digit LCD counter
Reset Function	Via magnet in lid
Units	Litres or Kilolitres

FRT303 Dual LCD Rate & Totals

Power	Lithium Battery (+9 yrs)
Mounting	Wall mount to IP67
Display	2 x Totalisers 1 x Reset 1 x Flow rate
Reset Function	Push button on front
Units	L, KL, L/ sec/ min/hr.
Outputs	Pulse/mA + low/hi.



Туре	Pre-set Microprocessor
Mounting	Panel Mount to IP64
Display	LCD Multi HMI
Units	Litres , mls, KL, Kg's
Optional Interface to PLC's	Start/stop/reset + Pulse 4-20mA

ME-USB5+ economy USB logger

Туре	USB event Logger
Power	Lithium
Application use	Download to PC
Time/Date/Log	Stores 1 million events



Enquire for:-

- GSM loggers
- other LCD reset counters
- other flow applications




Agricultural Applications:

- Irrigation Channels/Pipes
- River and Dam Water Usage
- Sprayer Irrigation Systems
- Nutrient & Fertiliser Dispensing
- Water Control for Cattle Feedlots
- Groundwater & Bore Extraction
- Truck Loading and Discharge
- Pump performance monitoring

Process Control:

- Batch Controller Systems
- Raw Water Pump Stations
- Rate-of-flow Indication / mA outputs
- PLC input scaling cards
- Custody transfer ticket printing options.







ManuFlo ®

- Australian company since 1965.
- Items stocked in Sydney
- · Free on-going product & application support.
- · Rapid personal service and phone support.
- Simple to use, proven product.
- Flowmeter and process control specialists.



Flow Measurement & Control Products

a division of

MANU ELECTRONICS PTY LTD

41 Carter Road, Brookvale Sydney NSW 2100 Australia Ph: +61 2 9905-4324, 9938-1425

Fax: + 61 2 9938-5852

Web: www.manuelectronics.com.au Email: sales@manuelectronics.com.au