

TTP-A5 Thermal Printer

FEATURES

- Panel-mount thermal printer.
- Easy paper loading via front panel.
- Low noise.
- Serial interface.
- During power on, hold and release paper feed button for a test print.



TTP-A5 Printer

Print Method	Thermal Direct Line
Character Height	3 mm
Thermal Paper (52g)	57mm wide x 46 mm φ
Paper Roll Diameter	Max: 50 mm
Effective Printing Width	48 mm
Resolution	8 dots/mm (203 DPI), 384 dots/line
Print Speed	50 - 80 mm/sec
Reliability (MCBF)	5 million lines
Interface	RS232C, 9600 baud
Panel Cut	82 x 82 mm
Outline Dimensions	88 x 87 x 56.5 mm
Imbedded Depth	53.5 mm
Operating Temp	5 °C to 50 °C
Storage Temp	-20 °C to 60 °C
Operating Humidity	10 - 80 %
Storage Humidity	10 - 90 %
Power	5 - 9 VDC
Weight (printer only)	0.2 kg

* BATCH DISPENSED *
B-0009 01/01/00 00:01
000017 L

Sample batch ticket printout



Power/Status
LED and
paperfeed
button

LED Blink Rate	Meaning
At power up: 2x at 1 second interval	Startup OK
Regular flashing	All OK
2 x	Printer mechanism error, or temperature too low
3 x	No paper
5 x	Printer overheated
6 x	Roller problem
10 x	Firmware error

Order Code

Description

TTP-A5	Serial printer (without power supply), with 1 roll of paper
T-ACPS	240 VAC power supply module for printer. 5VDC, 3 Amp output.
T-DCPS	12-24 VDC power supply module for printer. 5VDC, 3 Amp output.
T-TP	Thermal Paper for TTP-A5 thermal ticket printer (single roll)
T-TP50	Thermal Paper for TTP-A5 thermal ticket printer (box of 50 rolls)

Due to continuous product improvement, specifications are subject to change without notice.

ManuFlo®TM

Flow Measurement & Control Products

a division of

MANU ELECTRONICS PTY LTD

1408/2

41 Carter Road, Brookvale
Sydney NSW 2100 Australia
Ph: + 61 2 9905 4324, 9938 1425
Fax: + 61 2 9938 5852
Web: www.manuelectronics.com.au
Email: sales@manuelectronics.com.au